We claim:

An organic light emitting device comprising:

an anode;

a hole transporting layer over the anode, wherein the hole transporting layer is doped with a phosphorescent material;

an electron transporting layer over the hole transporting layer, wherein the electron transporting layer is doped with the phosphorescent material; and a cathode over the electron transporting layer.

The organic light emitting device of claim 1, wherein the organic light emitting device emits light in the blue range of the visible spectrum.

comprises a member of the group consisting of 4,4'-bis[N-(1-naphthyl)-N-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylpheny)1-1'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), -3-4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'-dimethylphenylphenyl (HMTPD), and 3,3'-Dimethyl-N⁴,N⁴,N⁴,N⁴,N⁴, N⁴ tetra-p-tolyl-biphenyl-4,4'-diamine (R854).

The organic light emitting device of claim 1, wherein the electron transporting layer comprises a member of the group consisting of an oxadiazole, an oxadiazole derivative, a phenanthroline, a substituted benzoxazole, an un-substituted benzoxazole,

Inventor search!

doping in both

1.

428/690 313/504 506 251/102

Show of showing the state of th

col college

NY01 354733 v 3

18

a substituted benzthiazole, and an un-substituted benzthiazole compound.

coli7 In 35 25

The organic light emitting device of claim 1, wherein the electron transporting layer comprises a member of the group consisting of 1,3-bis (N,N-t-butyl-phenyl)-1,3,4-oxadiazole (OXD-7), 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (bathocuproine or BCP), a BCP derivative, and 3-phenyl-4-(1'-naphthyl)-5-phenyl-1,2,4-triazole (TAZ).

The organic light emitting device of claim 1, wherein the phosphorescent material comprises a member of the group consisting of Platinum(II) (2-phenylpyridinato-N,C²) (acetyl acetonate) [Pt(ppy)(acac)], Platinum(II) (2-(p-tolyl)pyridinato-N,C²) (acetyl acetonate) [Pt(tpy)(acac)], Platinum(II) (7,8-benzoqionolinato-N,C³) (acetyl acetonate) [Pt(bzq)(acac)], Platinum(II) (2-(2'-(4',5'-benzothienyl)pyridinato-N,C³) (acetyl acetonate) [Pt(btp)(acac)], Platinum(II) (2-(4',6'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,6-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,5-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Pt(4,5-F₂ppy)(pico)], and Iridium (2-(4',6'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Ir(4,6-F₂ppy)(pico)].

singlet bother
ward
ward
provest
prove

The organic light emitting device of claim 1, wherein the cathode comprises a member (o 1 21 lm 5 10 31) of the group consisting of magnesium silver and a magnesium silver alloy, and the anode comprises indium tin oxide (ITO). (10 14 lm 51)

8. An electronic device incorporating the organic light emitting device of claim 1, the

19

electronic device selected from the group consisting of a billboard, a sign, a computer monitor, a vehicle, a telecommunications device, a telephone, a printer, a television, a large area wall screen, a theater screen and a stadium screen.

intended 102



An organic light emitting device comprising:

an anode;

a first hole transporting layer over the anode;

a second hole transporting layer over the first hole transporting layer, wherein the second hole transporting layer is doped with a phosphorescent material; a first electron transporting layer over the second hole transporting layer, wherein the first electron transporting layer is doped with the phosphorescent material; a second electron transporting layer over the first electron transporting layer; and a cathode over the second electron transporting layer.

10. The organic light emitting device of claim 9, wherein the organic light emitting device emits light in the blue range of the visible spectrum.

11.

The organic light emitting device of claim 9, wherein the first hole transporting layer comprises a member of the group consisting of 4,4'-bis[*N*-(1-naphthyl)-*N*-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylpheny)1-1'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), 4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'-dimethylbiphenyl (HMTPD), and 3,3'-Dimethyl-*N*⁴,*N*⁴,*N*^{4'},*N*^{4'}-tetra-*p*-tolyl-biphenyl-4,4'-diamine (R854), and wherein the second hole transporting

layer comprises a member of the group consisting of 4,4'-bis[N-(1-naphthyl)-N-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylpheny)1-1'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), 4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'-dimethylbiphenyl (HMTPD), and 3,3'-Dimethyl-N⁴,N⁴,N^{4'},N^{4'}-tetra-p-tolyl-biphenyl-4,4'-diamine (R854).

The organic light emitting device of claim 9, wherein the first hole transporting layer has an IP energy not more than about 0.7 eV greater than the IP energy of the anode.

The organic light emitting device of claim 12, wherein the first hole transporting layer has an IP energy not more than about 0.5 eV greater than the IP energy of the anode.

The organic light emitting device of claim 9, wherein the first electron transporting layer comprises a member of the group consisting of an oxadiazole, an oxadiazole derivative, a phenanthroline, a substituted benzoxazole, an un-substituted benzoxazole, a substituted benzthiazole, and an un-substituted benzthiazole compound, and wherein the second electron transporting layer comprises a member of the group consisting of tris-(8-hydroxyquinoline)aluminum (Alq₃) and a phthalocyanine compound.

The organic light emitting device of claim 9, wherein the first electron transporting layer comprises a member of the group consisting of 1,3-bis (N,N-t-butyl-phenyl)-1,3,4-oxadiazole (OXD-7), 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (bathocuproine or BCP), a BCP derivative, and 3-phenyl-4-(1'-naphthyl)-5-phenyl-

pterriod

prepterriod

p

TP greater from a reader to >> emitter

1,2,4-triazole (TAZ), and wherein the second electron transporting layer comprises copper phthalocyanine (CuPc).

16.

The organic light emitting device of claim 9, wherein the phosphorescent material comprises a member of the group consisting of Platinum(II) (2-phenylpyridinato-N,C²) (acetyl acetonate) [Pt(ppy)(acac)], Platinum(II) (2-(p-tolyl)pyridinato-N,C²) (acetyl acetonate) [Pt(tpy)(acac)], Platinum(II) (7,8-benzoqionolinato-N,C³) (acetyl acetonate) [Pt(bzq)(acac)], Platinum(II) (2-(2'-(4',5'-benzothienyl)pyridinato-N,C³) (acetyl acetonate) [Pt(btp)(acac)], Platinum(II) (2-(4',6'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,6-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,5-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Pt(4,5-F₂ppy)(pico)], and Iridium (2-(4',6'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Ir(4,6-F₂ppy)(pico)].

1/7

The organic light emitting device of claim 9, wherein the cathode comprises a member of the group consisting of magnesium silver and a magnesium silver alloy, and the anode comprises indium tin oxide (ITO).



An electronic device incorporating the organic light emitting device of claim 9, the electronic device selected from the group consisting of a billboard, a sign, a computer monitor, a vehicle, a telecommunications device, a telephone, a printer, a television, a large area wall screen, a theater screen and a stadium screen.



An organic light emitting device comprising:

a substrate;

an anode over the substrate;

a first hole transporting layer over the anode;

a second hole transporting layer over the first hole transporting layer, wherein the second hole transporting layer is doped with a phosphorescent material; a first electron transporting layer over the second hole transporting layer, wherein the first electron transporting layer is doped with the phosphorescent material; a second electron transporting layer over the first electron transporting layer; and a cathode over the second electron transporting layer.

The organic light emitting device of claim 19, wherein the organic light emitting device emits light in the blue range of the visible spectrum.

The organic light emitting device of claim 19, wherein the first hole transporting layer comprises a member of the group consisting of 4,4'-bis[N-(1-naphthyl)-N-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylpheny)1-1'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), 4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'-dimethylbiphenyl (HMTPD), and 3,3'-Dimethyl-N⁴,N⁴,N⁴,N⁴'-tetra-p-tolyl-biphenyl-4,4'-diamine (R854), and wherein the second hole transporting layer comprises a member of the group consisting of 4,4'-bis[N-(1-naphthyl)-N-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylphenyl-1-l'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), 4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-

(3-tolyl)amino]-3,3'-dimethylbiphenyl (HMTPD), and 3,3'-Dimethyl-N',N',N',N'-tetra-p-tolyl-biphenyl-4,4'-diamine (R854).

The organic light emitting device of claim 19, wherein the first hole transporting layer has an IP energy not more than about 0.7 eV greater than the IP energy of the anode.

The organic light emitting device of claim 22, wherein the first hole transporting layer has an IP energy not more than about 0.5 eV greater than the IP energy of the anode.

The organic light emitting device of claim 19, wherein the first electron transporting layer comprises a member of the group consisting of an oxadiazole, an oxadiazole derivative, a phenanthroline, a substituted benzoxazole, an un-substituted benzoxazole, a substituted benzthiazole, and an un-substituted benzthiazole compound, and wherein the second electron transporting layer comprises a member of the group consisting of tris-(8-hydroxyquinoline)aluminum (Alq₃) and a phthalocyanine compound.

The organic light emitting device of claim 19, wherein the first electron transporting layer comprises a member of the group consisting of 1,3-bis (N,N-t-butyl-phenyl)-1,3,4-oxadiazole (OXD-7), 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (bathocuproine or BCP), a BCP derivative, and 3-phenyl-4-(1'-naphthyl)-5-phenyl-1,2,4-triazole (TAZ), and wherein the second electron transporting layer comprises copper phthalocyanine (CuPc).

The organic light emitting device of claim 19, wherein the phosphorescent material

×26.

comprises a member of the group consisting of Platinum(II) (2-phenylpyridinato-N,C²) (acetyl acetonate) [Pt(ppy)(acac)], Platinum(II) (2-(p-tolyl)pyridinato-N,C²) (acetyl acetonate) [Pt(tpy)(acac)], Platinum(II) (7,8-benzoqionolinato-N,C³) (acetyl acetonate) [Pt(bzq)(acac)], Platinum(II) (2-(2'-(4',5'-benzothienyl)pyridinato-N,C³) (acetyl acetonate) [Pt(btp)(acac)], Platinum(II) (2-(4',6'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,6-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,5-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Pt(4,5-F₂ppy)(pico)], and Iridium (2-(4',6'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Ir(4,6-F₂ppy)(pico)].

27/

The organic light emitting device of claim 19, wherein the cathode comprises a member of the group consisting of magnesium silver and a magnesium silver alloy, and the anode comprises indium tin oxide (ITO).

28.

The organic light emitting device of claim 19, wherein the substrate comprises a member of the group consisting of plastic, metal and glass.

29.

The organic light emitting device of claim 19, wherein the substrate is substantially transparent.

30.

The organic light emitting device of claim 19, wherein the substrate is opaque, and the cathode is transparent.

31.

An electronic device incorporating the organic light emitting device of claim 19, the

electronic device selected from the group consisting of a billboard, a sign, a computer monitor, a vehicle, a telecommunications device, a telephone, a printer, a television, a large area wall screen, a theater screen and a stadium screen.

An organic light emitting device comprising:

a substrate;

a cathode over the substrate;

a first electron transporting layer over the cathode;

a second electron transporting layer over the first electron transporting layer, wherein the second electron transporting layer is doped with a phosphorescent material; a first hole transporting layer over the second electron transporting layer, wherein the first hole transporting layer is doped with the phosphorescent material; a second hole transporting layer over the first hole transporting layer; and an anode over the second hole transporting layer.

The organic light emitting device of claim 32, wherein the organic light emitting device emits light in the blue range of the visible spectrum.

34. The organic light emitting device of claim 32, wherein the first hole transporting layer comprises a member of the group consisting of 4,4'-bis[N-(1-naphthyl)-N-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylpheny)1-1'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), 4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'-dimethylbiphenyl (HMTPD), and 3,3'-Dimethyl-N⁴,N⁴,N⁴,N⁴'-

26

35. 36. tetra-*p*-tolyl-biphenyl-4,4'-diamine (R854), and wherein the second hole transporting layer comprises a member of the group consisting of 4,4'-bis[*N*-(1-naphthyl)-*N*-phenyl-amino]biphenyl (α-NPD), N,N'-diphenyl-N,N'-bis(3-methylpheny)1-1'biphenyl-4,4'diamine (TPD), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'- dimethylbiphenyl (M14), 4,4',4"-tris(30methylphenylphenylamino)triphenylamine (MTDATA), 4,4'-bis[N,N'-(3-tolyl)amino]-3,3'-dimethylbiphenyl (HMTPD), and 3,3'-Dimethyl-*N*⁴,*N*⁴,*N*⁴',*N*⁴'-tetra-*p*-tolyl-biphenyl-4,4'-diamine (R854).

36.

The organic light emitting device of claim 32, wherein the second hole transporting layer has an IP energy not more than about 0.7 eV greater than the IP energy of the anode.

The organic light emitting device of claim 35, wherein the second hole transporting layer has an IP energy not more than about 0.5 eV greater than the IP energy of the anode.



The organic light emitting device of claim 32, wherein the second electron transporting layer comprises a member of the group consisting of an oxadiazole, an oxadiazole derivative, a phenanthroline, a substituted benzoxazole, an un-substituted benzoxazole, a substituted benzthiazole, and an un-substituted benzthiazole compound, and wherein the first electron transporting layer comprises a member of the group consisting of tris-(8-hydroxyquinoline)aluminum (Alq₃) and a phthalocyanine compound.

20

The organic light emitting device of claim 32, wherein the second electron transporting

layer comprises a member of the group consisting of 1,3-bis (N,N-t-butyl-phenyl)-1,3,4-oxadiazole (OXD-7), 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (bathocuproine or BCP), a BCP derivative, and 3-phenyl-4-(1'-naphthyl)-5-phenyl-1,2,4-triazole (TAZ), and wherein the first electron transporting layer comprises copper phthalocyanine (CuPc).

The organic light emitting device of claim 32, wherein the phosphorescent material comprises a member of the group consisting of Platinum(II) (2-phenylpyridinato-N,C²) (acetyl acetonate) [Pt(ppy)(acac)], Platinum(II) (2-(p-tolyl)pyridinato-N,C²) (acetyl acetonate) [Pt(tpy)(acac)], Platinum(II) (7,8-benzoqionolinato-N,C³) (acetyl acetonate) [Pt(bzq)(acac)], Platinum(II) (2-(2'-(4',5'-benzothienyl)pyridinato-N,C³) (acetyl acetonate) [Pt(btp)(acac)], Platinum(II) (2-(4',6'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,6-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,5-F₂ppy)(acac)], Platinum(II) (2-(4',5'-difluorophenyl)pyridinato-N,C²) (acetyl acetonate) [Pt(4,5-F₂ppy)(pico)], and

The organic light emitting device of claim 32, wherein the cathode comprises a member of the group consisting of magnesium silver and a magnesium silver alloy, and the anode comprises indium tin oxide (ITO).

Iridium (2-(4',6'-difluorophenyl)pyridinato-N,C²) (2-picolinato) [Ir(4,6-F₂ppy)(pico)].

The organic light emitting device of claim 32, wherein the substrate comprises a member of the group consisting of plastic, metal and glass.

- 42. The organic light emitting device of claim 32, wherein the substrate is substantially transparent.
- 43. The organic light emitting device of claim 32, wherein the substrate is opaque, and the anode is transparent.
- 44. An electronic device incorporating the organic light emitting device of claim 32, the electronic device selected from the group consisting of a billboard, a sign, a computer monitor, a vehicle, a telecommunications device, a telephone, a printer, a television, a large area wall screen, a theater screen and a stadium screen.

claim	-	Claim 19:
	Conthode transport layer Phosphor hole transport layer Phosphor HTL Anode	Contracts Ind transport Istransport (phosphor) Ind hole (phosphor) Ist-hole anode I Substrate

Claim 9:

Cathode 2nd transport 1st transport(phosphor) 2nd hole (phosphor) 1st hole Anode Claim 32:

	· j
٦	anode
•	2nd hole
	1 1st hole (phosphor)
	I and transport (phosphor)
	1 1st transport
	Touthode
ĺ	Substrate